

Type:

# BSS210

surface, pendant, or cable mount ready,  
square top, linear T5 LED fixture with lens



### SPECIFICATIONS

- Fully assembled aluminum extruded housing
- Standard finish is high reflectance white powder coat, applied post production
- Knock-outs accept standard electrical fittings (by others)
- Includes frosted acrylic lens
- LEDs are available in 3,000K, 3500K, 4,000K and 5,000K color temperatures
- Available in standard white, black, silver, platinum, bronze and primer powder coat, applied post production (consult factory for custom finishes)
- Lamp life is rated at 50,000 hours
- Limited 3 year warranty
- UL listed for dry and damp locations
- IBEW manufactured and labeled
- Universal voltage driver
- 0-10V dimming
- Made in the U.S.A.

### PERFORMANCE

- 1100 Lm/ft.
- 9.1 w/ ft.
- 80 CRI

Specification order example: BSS200S + 2 + 30 + D + SM + WH + OCC

	NOMINAL FIXTURE LENGTH	COLOR TEMPERATURE	DIMMING	MOUNTING	FINISH	OPTIONS
BSS210	+	+	+	+	+	+
	<ul style="list-style-type: none"> <li>— 2'</li> <li>— 3'</li> <li>— 4'</li> <li>— 5'</li> <li>— 6'</li> <li>— 7'</li> <li>— 8'</li> </ul>	<ul style="list-style-type: none"> <li>— 30: 3,000K</li> <li>— 35: 3,500K</li> <li>— 40: 4,000K</li> <li>— 50: 5,000K</li> </ul>	<ul style="list-style-type: none"> <li>— D: dimming</li> <li>— leave blank for no dimming</li> </ul>	<ul style="list-style-type: none"> <li>— SM: surface mount</li> <li>— CM: cable mount</li> </ul>	<ul style="list-style-type: none"> <li>— WH: white</li> <li>— FW: fluoro scape white</li> <li>— BL: black</li> <li>— SL: silver</li> <li>— PT: platinum</li> <li>— BZ: bronze</li> <li>— PR: primer</li> <li>— CF: consult factory for custom color</li> </ul>	<ul style="list-style-type: none"> <li>— OCC: occupancy sensor</li> </ul>

