

Type:

BSS210

surface, pendant, or cable mount ready, square top, linear LED fixture with lens



SPECIFICATIONS

- Fully assembled aluminum extruded housing
- Includes frosted acrylic lens
- LEDs are available in 3,000K, 3500K, 4,000K and 5,000K color temperatures
- Available in standard white, black, silver, platinum, bronze and primer powder coat, applied post production (consult factory for custom finishes)
- LED is rated at 50,000 hours
- Limited 3 year warranty
- UL listed for dry and damp locations
- IBEW manufactured and labeled
- Universal voltage driver
- 0-10V dimming optional
- Made in the U.S.A.

PERFORMANCE

- 1100 Lm/ft.
- 9.1 w/ ft.
- 80 CRI

Specification order example: BSS210 + 2 + 30 + D + SM + WH + OCC

	NOMINAL FIXTURE LENGTH	COLOR TEMPERATURE	DIMMING	MOUNTING	FINISH	OPTIONS
BSS210	+	+	+	+	+	+
	<ul style="list-style-type: none"> — 2' — 3' — 4' — 5' — 6' — 7' — 8' 	<ul style="list-style-type: none"> — 30: 3,000K — 35: 3,500K — 40: 4,000K — 50: 5,000K 	<ul style="list-style-type: none"> — D: dimming — leave blank for no dimming 	<ul style="list-style-type: none"> — SM: surface mount — CM: cable mount — PM: pendant mount — SRM: semi-recessed mount 	<ul style="list-style-type: none"> — WH: white — FW: fluoroscape white — BL: black — SL: silver — PT: platinum — BZ: bronze — PR: primer — CF: consult factory for custom color 	<ul style="list-style-type: none"> — OCC: occupancy sensor

