

Type:

BSS210

surface, pendant, or cable mount ready,
square top, linear T5 LED fixture with lens



SPECIFICATIONS

- Fully assembled housing is formed and welded, 20 ga. steel, chemically treated to resist corrosion and enhance paint adhesion
- Standard finish is high reflectance white powder coat, applied post production
- Knock-outs accept standard electrical fittings (by others)
- Includes frosted acrylic lens
- LEDs are available in 2,700K, 3,000K, 3500K, 4,000K and 5,000K (±200K) color temperatures
- Available in standard white, black, silver, platinum, bronze and primer powder coat, applied post production (consult factory for custom finishes)
- Lamp life is rated at 50,000 hours
- Limited 3 year warranty
- UL listed for dry and damp locations
- IBEW manufactured and labeled
- Made in the U.S.A.


PERFORMANCE

- Direct line voltage LED lamp does NOT need an external driver
- Operating voltage 120V
- Available at 20mA or 60mA output

Specification order example: BSS200S + 2 + 2,700K + 20 + WH

	NOMINAL FIXTURE LENGTH	COLOR TEMPERATURE	CURRENT	FINISH
BSS210	+	+	+	+
	<ul style="list-style-type: none"> — 2': 20-1/16" — 3': 31-7/8" — 4': 43-5/8" 	<ul style="list-style-type: none"> — 27: 2,700K — 30: 3,000K — 35: 3,500K — 40: 4,000K — 50: 5,000K 	<ul style="list-style-type: none"> — 20: 20mA — 60: 60mA 	<ul style="list-style-type: none"> — WH: white — BL: black — SL: silver — PT: platinum — BZ: bronze — PR: primer — CF: consult factory for custom color

Profile



Plan



Side

