

Type:



- Fully assembled housing is formed and welded, 20 ga. steel, chemically treated to resist corrosion and enhance paint adhesion
- Model variations offered for surface, cable suspended and pendant mount applications
- Available in standard white, black, silver, platinum, bronze and primer powder coat, applied post production (consult factory for custom finishes)
- Available for one T5 14W, 21W, 28W, 35W and high output 24W, 39W, 54W and 80W linear fluorescent lamps
- Standard ballast is specification grade 120V-277V program start (consult factory for other voltage options)
- Dimming, emergency battery backup and specialized ballast factor options available (consult factory for availability and system compatibility)
- Knock-outs on back accept standard electrical fittings by others (consult factory for other locations)
- Rotational locking lamp holders
- UL and C-UL listed for dry and damp locations
- IBEW manufactured and labeled
- Made in the U.S.A.

IEL5S +						
	Section 1	Section 2	Section 3*	Section 4	Section 5	
	<ul style="list-style-type: none"> — 14W: 22-9/16" — 21W: 34-3/8" — 28W: 46-3/16" — 35W: 58" — 24W: 22-9/16" — 39W: 34-3/8" — 54W: 46-3/16" — 80W: 58" 	<ul style="list-style-type: none"> — U: 120V-277V — 347: 347V — CF: consult factory for specialize voltage 	<ul style="list-style-type: none"> [Non-Dimming] — PRS: program rapid start [Dimming] — MKX: Advance Mark 10 — VII: Advance Mark 7 — H300: Lutron Hi-Lume 3D — EHD: Lutron EcoSystem H — ESYS: Lutron EcoSystem — DALI: Dali T5 — PHO: Sylvania Helios — TEN: Universal Super Dim 	<ul style="list-style-type: none"> [Custom Performance] — PN85: .85BF program start — PN90: .90BF program start [Emergency] — I28: Iota ISL-28 — I54: Iota ISL-54 — I540: Iota ISL-540-35W — L50: Bodine LP500 — L55: Bodine LP550 — L60: Bodine LP600 — L60S: Bodine LP600STU 	<ul style="list-style-type: none"> — SM: surface mount — CM48: cable mount 48" cable length — CM96: cable mount 96" cable length — PMX: pendant mount 18" stem length — PMX: pendant mount 18" stem length — PMX: pendant mount 18" stem length — CF: consult factory for custom length 	<ul style="list-style-type: none"> — WH: white — BL: black — SL: silver — PT: platinum — BZ: bronze — PR: primer — CF: consult factory for custom color

*Not all ballasts work with all lamps. Consult factory details.

