

Type:



- Fully assembled housing is formed and welded, 20 ga. steel, chemically treated to resist corrosion and enhance paint adhesion
- Model variations offered for surface, cable suspended and pendant mount applications
- Available in standard white, black, silver, platinum, bronze and primer powder coat, applied post production (consult factory for custom finishes)
- Available for one T5 14W, 21W, 28W, 35W and high output 24W, 39W, 54W and 80W linear fluorescent lamps
- Standard ballast is specification grade 120V-277V program start (consult factory for other voltage options)
- Dimming, emergency battery backup and specialized ballast factor options available (consult factory for availability and system compatibility)
- Knock-outs on back accept standard electrical fittings by others (consult factory for other locations)
- Rotational locking lamp holders
- UL and C-UL listed for dry and damp locations
- IBEW manufactured and labeled
- Made in the U.S.A.

<b>IEL5S +</b>						
	<b>Section 1</b>	<b>Section 2</b>	<b>Section 3*</b>	<b>Section 4</b>	<b>Section 5</b>	
	<ul style="list-style-type: none"> <li>14W: 22-9/16"</li> <li>21W: 34-3/8"</li> <li>28W: 46-3/16"</li> <li>35W: 58"</li> <li>24W: 22-9/16"</li> <li>39W: 34-3/8"</li> <li>54W: 46-3/16"</li> <li>80W: 58"</li> </ul>	<ul style="list-style-type: none"> <li>U: 120V-277V</li> <li>347: 347V</li> <li>CF: consult factory for specialize voltage</li> </ul>	<ul style="list-style-type: none"> <li><b>[Non-Dimming]</b></li> <li>PRS: program rapid start</li> <li><b>[Dimming]</b></li> <li>MKX: Advance Mark 10</li> <li>VII: Advance Mark 7</li> <li>H300: Lutron Hi-Lume 3D</li> <li>EHD: Lutron EcoSystem H</li> <li>ESYS: Lutron EcoSystem</li> <li>DALI: Dali T5</li> <li>PHO: Sylvania Helios</li> <li>TEN: Universal Super Dim</li> </ul>	<ul style="list-style-type: none"> <li><b>[Custom Performance]</b></li> <li>PN85: .85BF program start</li> <li>PN90: .90BF program start</li> <li><b>[Emergency]</b></li> <li>I28: Iota ISL-28</li> <li>I54: Iota ISL-54</li> <li>I540: Iota ISL-540-35W</li> <li>L50: Bodine LP500</li> <li>L55: Bodine LP550</li> <li>L60: Bodine LP600</li> <li>L60S: Bodine LP600STU</li> </ul>	<ul style="list-style-type: none"> <li>SM: surface mount</li> <li>PMX: pendant mount 18" stem length</li> <li>PMX: pendant mount 18" stem length</li> <li>PMX: pendant mount 18" stem length</li> <li>CF: consult factory for custom length</li> </ul>	<ul style="list-style-type: none"> <li>WH: white</li> <li>BL: black</li> <li>SL: silver</li> <li>PT: platinum</li> <li>BZ: bronze</li> <li>PR: primer</li> <li>CF: consult factory for custom color</li> </ul>

\*Not all ballasts work with all lamps. Consult factory details.

