



8165 E. Kaiser Blvd. Anaheim, CA 92808
 p. 714.282.2270
 f. 714.676.5558

Photometric Test Report

IES INDOOR REPORT
PHOTOMETRIC FILENAME : L031505101.IES

DESCRIPTION INFORMATION (From Photometric File)

IESNA:LM-63-2002
 [TEST] L031505101
 [TESTLAB] LIGHT LABORATORY, INC.
 [ISSUEDATE] 3/17/2015
 [MANUFAC] BARTCO LIGHTING
 [LUMCAT] BSS215
 [LUMINAIRE] 3"L. X 44-1/2"W. X 4"H. LED LUMINAIRE
 [MORE] DIFFUSED LENS
 [BALLASTCAT] PHILIPS ADVANCE XI054C150V054DNT1
 [BALLAST] INPUT: 120-277VAC, 0.54-0.23A, 50/60Hz. OUTPUT: 0.7-1.5ADC, 27-54VDC
 [LAMPPOSITION] 0,0
 [LAMPCAT] N/A
 [OTHER] INDICATING THE CANDELA VALUES ARE ABSOLUTE AND
 [MORE] SHOULD NOT BE FACTORED FOR DIFFERENT LAMP RATINGS.
 [_INPUT] 120VAC, 40.96W
 [_TEST PROCEDURE] IESNA:LM-79-08

CHARACTERISTICS

Lumens Per Lamp	N.A. (absolute)
Total Lamp Lumens	N.A. (absolute)
Luminaire Lumens	4189
Total Luminaire Efficiency	N.A.
Luminaire Efficacy Rating (LER)	102
Total Luminaire Watts	40.96
Ballast Factor	1.00
CIE Type	Semi-Direct
Spacing Criterion (0-180)	1.20
Spacing Criterion (90-270)	1.14
Spacing Criterion (Diagonal)	1.30
Basic Luminous Shape	Rectangular w/Sides
Luminous Length (0-180)	0.25 ft
Luminous Width (90-270)	3.67 ft
Luminous Height	0.17 ft

IES INDOOR REPORT
PHOTOMETRIC FILENAME : L031505101.IES

LUMINANCE DATA (cd/sq.m)

Angle In Degrees	Average 0-Deg	Average 45-Deg	Average 90-Deg
45	8268	8148	10107
55	7671	7038	8337
65	6950	6097	6660
75	5914	5232	5019
85	4737	4463	3165

**IES INDOOR REPORT
PHOTOMETRIC FILENAME : L031505101.IES**

CANDELA TABULATION

	<u>0</u>	<u>5</u>	<u>10</u>	<u>15</u>	<u>20</u>	<u>25</u>	<u>30</u>	<u>35</u>	<u>40</u>	<u>45</u>
0	1283	1283	1283	1283	1283	1283	1283	1283	1283	1283
5	1281	1281	1281	1281	1280	1280	1280	1280	1279	1278
10	1259	1259	1259	1259	1258	1258	1257	1257	1256	1256
15	1216	1216	1216	1216	1215	1215	1217	1216	1215	1215
20	1156	1156	1156	1155	1156	1156	1156	1154	1153	1152
25	1086	1086	1085	1085	1085	1085	1082	1081	1080	1078
30	1015	1014	1013	1013	1011	1007	1005	1002	1000	997
35	948	947	945	943	938	933	928	922	916	910
40	889	888	885	880	872	864	856	845	835	826
45	838	836	832	825	814	802	789	774	759	744
50	790	788	783	773	760	744	727	708	688	669
55	740	738	732	721	706	687	667	644	620	597
60	683	680	674	663	647	628	607	582	555	528
65	616	614	608	598	583	565	543	518	490	462
70	541	540	535	526	513	496	477	453	426	398
75	462	460	456	449	439	425	408	387	363	337
80	383	382	379	374	367	356	342	324	304	280
85	309	309	307	304	299	291	280	265	248	228
90	247	246	245	243	240	234	225	214	199	182
95	211	211	210	209	206	202	196	187	175	161
100	185	185	184	183	182	178	174	166	157	145
105	166	165	165	164	163	160	156	150	141	131
110	151	151	151	150	148	146	142	136	128	119
115	140	140	139	138	136	133	130	124	117	109
120	130	130	129	128	126	123	119	113	107	99
125	120	120	119	117	115	112	108	103	97	90
130	110	110	109	107	105	102	98	93	87	81
135	99	99	98	97	94	91	88	83	78	71
140	88	88	87	86	83	81	77	73	67	60
145	77	77	76	74	72	70	66	61	56	51
150	65	65	64	63	61	58	54	50	46	42
155	54	54	53	52	50	46	43	40	37	35
160	43	43	42	41	38	35	33	32	30	28
165	32	32	31	29	27	26	25	24	23	21
170	22	22	20	19	18	18	18	17	16	15
175	12	11	11	11	11	11	11	11	10	10
180	0	0	0	0	0	0	0	0	0	0

Vert. Horizontal Angles

	<u>50</u>	<u>55</u>	<u>60</u>	<u>65</u>	<u>70</u>	<u>75</u>	<u>80</u>	<u>85</u>	<u>90</u>
0	1283	1283	1283	1283	1283	1283	1283	1283	1283
5	1277	1277	1276	1275	1275	1274	1273	1273	1273
10	1256	1255	1253	1251	1249	1248	1247	1246	1245
15	1212	1210	1208	1206	1204	1202	1199	1196	1195
20	1151	1150	1148	1145	1142	1140	1136	1133	1131
25	1077	1075	1073	1070	1066	1061	1057	1052	1049
30	993	990	986	982	977	972	966	960	956
35	904	899	893	887	881	874	867	859	854
40	816	807	798	789	780	771	762	753	746
45	730	717	704	692	680	669	657	647	638
50	649	631	614	598	583	569	556	543	534
55	573	551	529	510	492	476	460	446	435
60	501	476	452	429	409	389	372	356	345

**IES INDOOR REPORT
PHOTOMETRIC FILENAME : L031505101.IES**

CANDELA TABULATION - (Cont.)

65	434	406	380	355	332	311	292	276	264
70	369	341	314	288	264	242	222	205	192
75	309	281	255	228	204	181	161	144	130
80	255	229	202	176	152	129	109	92	78
85	205	181	156	131	108	86	66	49	36
90	162	141	118	95	73	52	33	16	0
95	144	126	106	86	67	47	30	14	0
100	130	114	97	79	61	44	28	14	0
105	118	104	89	73	57	41	26	13	0
110	108	95	82	67	53	38	25	12	0
115	98	87	75	62	49	35	23	11	0
120	90	79	68	56	45	32	21	11	0
125	81	72	62	51	41	30	19	10	0
130	73	64	55	45	36	26	17	9	0
135	63	55	48	39	31	23	15	8	0
140	54	47	40	34	27	20	14	8	0
145	45	40	34	29	23	17	12	8	0
150	38	34	29	24	19	15	11	7	0
155	32	27	24	20	17	13	10	7	0
160	25	22	20	17	14	12	9	7	0
165	19	18	16	14	12	10	8	7	0
170	14	13	12	11	10	9	8	7	0
175	10	9	9	8	8	8	8	8	0
180	0	0	0	0	0	0	0	0	0

IES INDOOR REPORT
PHOTOMETRIC FILENAME : L031505101.IES

ZONAL LUMEN SUMMARY

Zone	Lumens	%Lamp	%Fixt
0-20	461.80	N.A.	11.00
0-30	956.71	N.A.	22.80
0-40	1525.78	N.A.	36.40
0-60	2636.72	N.A.	62.90
0-80	3429.77	N.A.	81.90
0-90	3655.38	N.A.	87.30
10-90	3534.19	N.A.	84.40
20-40	1063.98	N.A.	25.40
20-50	1640.35	N.A.	39.20
40-70	1563.15	N.A.	37.30
60-80	793.05	N.A.	18.90
70-80	340.84	N.A.	8.10
80-90	225.61	N.A.	5.40
90-110	270.05	N.A.	6.40
90-120	362.76	N.A.	8.70
90-130	432.98	N.A.	10.30
90-150	511.59	N.A.	12.20
90-180	533.67	N.A.	12.70
110-180	263.62	N.A.	6.30
0-180	4189.05	N.A.	100.00

Total Luminaire Efficiency = N.A.%

ZONAL LUMEN SUMMARY

Zone	Lumens
0-10	121.18
10-20	340.62
20-30	494.91
30-40	569.07
40-50	576.37
50-60	534.57
60-70	452.20
70-80	340.84
80-90	225.61
90-100	151.88
100-110	118.17
110-120	92.72
120-130	70.22
130-140	48.78
140-150	29.83
150-160	15.29
160-170	5.82
170-180	0.97


IES INDOOR REPORT
PHOTOMETRIC FILENAME : L031505101.IES

COEFFICIENTS OF UTILIZATION - ZONAL CAVITY METHOD

Effective Floor Cavity Reflectance 0.20

RC	80				70				50			30			10			0	
	RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30		10
0	116	116	116	116	116	112	112	112	112	104	104	104	97	97	97	90	90	90	87
1	104	99	94	89	89	100	95	91	87	89	85	82	82	80	77	77	75	72	69
2	94	85	78	72	72	90	82	76	70	77	71	66	71	67	63	67	63	60	57
3	86	75	66	59	59	82	72	64	58	67	61	55	63	57	53	59	54	50	47
4	78	66	57	50	50	75	64	55	49	60	53	47	56	50	45	52	47	43	40
5	72	59	50	43	43	69	57	49	42	53	46	41	50	44	39	47	42	37	35
6	67	53	44	38	38	64	51	43	37	48	41	36	45	39	34	43	37	33	31
7	62	48	39	33	33	59	47	38	33	44	37	31	41	35	30	39	34	29	27
8	57	44	35	30	30	55	43	35	29	40	33	28	38	32	27	36	30	26	24
9	54	40	32	27	27	52	39	31	26	37	30	25	35	29	25	33	28	24	22
10	50	37	29	24	24	48	36	29	24	34	28	23	33	27	22	31	26	22	20

POLAR GRAPH



Maximum Candela = 1283 Located At Horizontal Angle = 0, Vertical Angle = 0

1 - Vertical Plane Through Horizontal Angles (0 - 180) (Through Max. Cd.)

2 - Vertical Plane Through Horizontal Angles (90 - 270)

3 - Horizontal Cone Through Vertical Angle (0) (Through Max. Cd.)