

Type:



BSS305

Low profile LED fixture



- Fully assembled housing is formed and welded, 20 ga. steel, chemically treated to resist corrosion and enhance paint adhesion
- Standard finishes white, black, or silver powder coat, applied post production
- Standard driver offered with 0-10V dimming or non-dim
- Knock-outs accept standard electrical fittings (by others)
- Frosted or prismatic lay-in lens
- Lamp life is rated at 50,000 hours
- 120-277V
- 400-600 lm /ft.
- 4-6 watts/ ft.
- Limited five year warranty
- UL and ULC listed for dry and damp locations
- IBEW manufactured and labeled
- Made in the U.S.A.

	NOM. LENGTH	COLOR TEMPERATURE	DRIVER	LENS	OPTIONS	FINISH
BSS305	+	+	+	+	+	+
	<ul style="list-style-type: none"> — 2' — 3' — 4' 	<ul style="list-style-type: none"> — 30: 3000K — 35: 3500K — 40: 4000K 	<ul style="list-style-type: none"> — [Non-Dimming] leave blank for non-dimming — [Dimming] <ul style="list-style-type: none"> — DIM: Advance 0-10V — ESYS: Lutron EcoSystem 5-Series — HLM: Lutron Hi-lume A-Series 	<ul style="list-style-type: none"> — C: clear — PR: linear prismatic 	<ul style="list-style-type: none"> — SW: Rocker Switch — OC: Occupancy Sensor 	<ul style="list-style-type: none"> — WH: white powdercoat — BL: black powdercoat — SL: silver powdercoat

Profile

