

# BSW208 | FATHOM

2" wide LED luminaire with flush lens, outdoor locations, remote driver



Project: \_\_\_\_\_ Type: \_\_\_\_\_



## FEATURES

The BSW208 is a linear LED luminaire for outdoor applications. The surface mount 2" wide by 3" tall extrusion is fitted with a flush, frosted lens and machined aluminum end caps. Each fixture is paired with a remote mounted wet location 0-10V dimming or non-dimming driver and housing.

## SPECIFICATIONS

Fixture constructed of an extruded aluminum housing, extruded, frosted acrylic lens and machined aluminum end caps

Standard finishes as shown below

Available for surface mounting in nominal lengths of 2'-8' single fixtures and continuous runs

Fixtures wired with 10' low voltage leads

Included remote 120-277V wet location driver offered with 0-10V dimming or non-dim and surface mount aluminum enclosure

Standard outputs are 345, 690 and 925 lumens per foot


LEDs available in 2700K, 3000K, 3500K and 4000K, within a 3 step MacAdam ellipse, all with 80+ CRI typical

Life: 50,000 hours L<sub>70</sub>

Limited five year warranty

UL and C-UL listed for wet locations

## SECTION



## PERFORMANCE

Note: All data reflects fixtures with 3500K LEDs

NOMINAL LENGTH	OUTPUT	LUMENS/ft.	WATTS/ft.	LUMINAIRE LUMENS	EFFICACY (LPW)
4'	L: low	345	4.0	1382	87
	R: regular	690	8.0	2759	86
	H: high	925	10.7	3694	87



## BSW208 -

### NOMINAL FIXTURE LENGTH\*

- 2: 24-5/8"
- 3: 36-5/8"
- 4: 48-5/8"
- 5: 60-5/8"
- 6: 72-5/8"
- 7: 84-5/8"
- 8: 96-5/8"

### CORRELATED COLOR TEMPERATURE

- 27: 2700K-80+ CRI
- 30: 3000K-80+ CRI
- 35: 3500K-80+ CRI
- 40: 4000K-80+ CRI

### DRIVER

- [remote]
- RN: non-dimming
- RD: 0-10V dimming, 5%

### LIGHT OUTPUT (lumens per foot)

- L: low - 345
- R: regular - 690
- H: high - 925

### MOUNT

- SM: surface mount

### RUN CONFIGURATION

- SN: single
- ST: starter
- AD: adder
- TR: terminator

### FINISH

- AW: architectural white (semi-matte)
- WH: white (semi-gloss)
- BL: black (semi-matte)
- MB: matte black
- ESS: environmental satin silver
- BZ: bronze
- PR: primer
- CF: consult factory for custom finish

Note: Each fixture includes a remote driver matched for fixture length and light output  
\* Actual dimension dependent on run configuration


# BSW208 | FATHOM

2" wide LED luminaire with flush lens, outdoor locations, remote driver

## MOUNTING

### ORDERING CODE

### DESCRIPTION



SM

### SURFACE MOUNT

- Use appropriate fastener through  $\varnothing 3/16$ " holes in housing
- 10' low voltage leads exit out the rear at an end

## EPA CALCULATIONS

LENGTH ORDERING CODE	EPA
2	0.99 ft <sup>2</sup>
3	1.46 ft <sup>2</sup>
4	1.94 ft <sup>2</sup>
5	2.42 ft <sup>2</sup>
6	2.89 ft <sup>2</sup>
7	3.36 ft <sup>2</sup>
8	3.84 ft <sup>2</sup>

## LENGTH/MOUNTING DIMENSIONS


ORDERING CODE	LENGTH A	LENGTH B	LENGTH C	LENGTH D	LENGTH E
2	24-5/8"	24-5/16"	24"	22"	18"
3	36-5/8"	36-5/16"	36"	34"	30"
4	48-5/8"	48-5/16"	48"	46"	42"
5	60-5/8"	60-5/16"	60"	58"	54"
6	72-5/8"	72-5/16"	72"	70"	66"
7	84-5/8"	84-5/16"	84"	82"	78"
8	96-5/8"	96-5/16"	96"	94"	90"

## RUN CONFIGURATION INFORMATION


ORDERING CODE	DESCRIPTION
SN	Single
ST	Starter
AD	Adder
TR	Terminator

## RUN INFORMATION


Back Plan - Surface Mount Single Fixture Option



Back Plan - Surface Mount Continuous Run Option



Plan - Wall Mount Single Fixture Option



Plan - Wall Mount Continuous Run Option

