


Project: _____ Type: _____



FEATURES

The Grom series GRM10 is a miniature, linear architectural luminaire for general lighting use. The 1-1/8" square extruded aluminum fixture is available for surface or cable mounting. Multiple remote driver options, 90+ CRI color temperatures, light outputs and finishes broaden application possibilities.

SPECIFICATIONS

Fixture constructed of an extruded aluminum housing, extruded acrylic lens and machined aluminum end caps

Model variations offered for surface and cable suspended applications

Standard finishes as shown below

Surface mount models install with spring clips, are wired with 10' low voltage leads and available with back or end feed options

Included standard remote 120-277V driver offered with 0-10V dimming or non-dim (other dimming driver options available)

Remote mounted emergency battery backup available (ordered separately, consult factory for details)

Standard outputs are 350 and 600 lumens per foot


LEDs available in 2700K, 3000K, 3500K and 4000K, within a 3 step MacAdam ellipse, all with 90+ CRI typical

Life: 50,000 hours L₇₀

Limited five year warranty

UL and C-UL listed for dry and damp locations

SECTION



PERFORMANCE

Note: All data reflects fixtures with 3500K LEDs

NOMINAL LENGTH	OUTPUT	LUMENS/ft.	WATTS/ft.	LUMINAIRE LUMENS	EFFICACY (LPW)
4'	R: regular	350	4.3	1296	81
	H: high	600	7.9	2216	76



GRM10 -

NOMINAL FIXTURE LENGTH*	CORRELATED COLOR TEMPERATURE	REMOTE DRIVER	LENS	MOUNT	RUN CONFIGURATION	FINISH
23: 22-5/8"	27: 2700K-90+ CRI	ND: non-dimming	A: flush lens	S1: surface mount back feed (SN only)	SN: single	AW: architectural white (semi-matte)
28: 28-1/8"	30: 3000K-90+ CRI	[Dimming]		S2: surface mount end feed (SN only)	ST: starter	WH: white (semi-gloss)
34: 33-5/8"	35: 3500K-90+ CRI	DM: 0-10V, 1%		C4: cable mount 4' cable length	AD: adder	BL: black (semi-matte)
39: 39-1/8"	40: 4000K-90+ CRI	HES: Lutron EcoSystem, soft-on/fade-to-black, 1%		C8: cable mount 8' cable length	TR: terminator	MB: matte black
45: 44-5/8"		H2: Lutron Hi-lume 2-wire forward phase, 1%, (120V ONLY)	LIGHT OUTPUT (lumens per foot)	CF: consult factory for custom mounting		ESS: environmental satin silver
50: 50-1/8"		EL: eldoLED ECOdrive 0-10V, 1%	R: regular - 350			BZ: bronze
56: 55-5/8"		ES: eldoLED SOLOdrive 0-10V, 0.1%	H: high - 600			PR: primer
61: 61-1/8"		ELD: eldoLED ECOdrive DALI, 1%	CF: consult factory for custom output			CF: consult factory for custom finish
67: 66-5/8"		ESD: eldoLED SOLOdrive DALI, 0.1%				SA: satin anodize (may require additional lead time)
72: 72-1/8"						
78: 77-5/8"						
83: 83-1/8"						
89: 88-5/8"						
RUN ‡						

Note: Each fixture includes a remote driver matched for fixture length and light output


* Actual dimension dependent on run configuration

‡ Specify run length to the nearest 1". Factory will configure using the least quantity of fixtures as close to the desired run length as possible. Run to be confirmed with a shop drawing.

MOUNTING

ORDERING CODE

DESCRIPTION




S1

SURFACE MOUNT – BACK FEED

Mounting option includes:

- Available for Single (SN) fixtures only
- 10' low voltage leads exiting from the fixture back at an end
- One pair spring mounting clips for horizontal mounting (natural finish, requires #6 flat head screws by others)




S2

SURFACE MOUNT – END FEED

Mounting option includes:

- Available for Single (SN) fixtures only
- 10' low voltage leads exiting from the fixture end
- One pair spring mounting clips for horizontal mounting (natural finish, requires #6 flat head screws by others)



C4 and C8

CABLE MOUNT

Mounting option includes:

- Ø 1/32" x 48" (C4) or 96" (C8) aircraft cables
- 60" (C4) or 108" (C8) low voltage cable (in coordinating finish)
- Bracket bars
- Ø 5" white canopies
- Canopy mount cable grippers

LENGTH/MOUNTING DIMENSIONS

ORDERING CODE	LENGTH A	LENGTH B
23	22-5/8"	22-1/4"
28	28-1/8"	27-3/4"
34	33-5/8"	33-1/4"
39	39-1/8"	38-3/4"
45	44-5/8"	44-1/4"
50	50-1/8"	49-3/4"
56	55-5/8"	55-1/4"
61	61-1/8"	60-3/4"
67	66-5/8"	66-1/4"
72	72-1/8"	71-3/4"
78	77-5/8"	77-1/4"
83	83-1/8"	82-3/4"
89	88-5/8"	88-1/4"


Note: Surface mount (S1, S2) luminaires available as Single (SN) fixtures ONLY – Reference Length A

RUN CONFIGURATION INFORMATION


ORDERING CODE	DESCRIPTION
SN	Single
ST	Starter
AD	Adder
TR	Terminator

RUN INFORMATION

Side View - S1 Surface Mount Single Fixture




Side View - S2 Surface Mount Single Fixture




RUN INFORMATION

Side View - Cable Mount Single Fixture



SN

Side View - Cable Mount Continuous Run



ST

AD

TR